


INDOOR BOX (MULTI-CLIENT-  
MULTI-OPERATOR) : 48 PORTS -  
48 FUSIONS\_ IP54 + ADAPTERS  
(FEMALE - FEMALE) SC/APC  
Manual & Information



## Contents

1	Features	3
1.1	Application /Construction	3
1.2	Characteristics	4
1.3	Advantages	4





# 1 Features

## 1.1 Application /Construction

Multioperator Distribution Cabinet up to 48 fibres

48 services Multioperator box for indoor installations in buildings.

Connection for multiple operators and subscribers.

It is a polycarbonate cabinet with dimensions of 450 x 180 x 150 mm and allows the installation of any indoor optical network technology.

Any indoor optical network technology.

These indoor boxes, which have been manufactured mainly for GPON and FTTH, allow the connection between multiple operators and subscribers.

FTTH, allowing connection between multiple operators and customers.

They have compartments separated by a splitter panel for up to 48 fibre optic cables and allow the installation of cables by fusion or direct connectorisation.

<b>Name</b>	Indoor Box (Multi-Client-Multi-operator) : 48 ports - 48 fusions_ IP54 + Adapters (female - female) SC/APC
<b>Aplication</b>	Indoor installation
<b>Photos</b>	



## 1.2 Characteristics

Made of grey polycarbonate body.

Capacity for 48 SC optical connectors

Support for SC simplex connectors

Operator part separated from residential distribution.

Common operator access to residential distribution

Fully compatible with PON or Point-to-Point architecture

Versatile to install any residential distribution technology (EasyBend cables, Riser cables, Riser cables, EasyBend cables, EasyBend cables, Riser cables

EasyBend cables, Riser cables, microduts, ribbon and slack cables)

Possibility to install splitters

Sealing Structure IP50.

Quick and easy installation

## 1.3 Advantages

- Capacity for 48 adapters with 6 trays for 16 fusions each
- Rugged, heavy-duty polycarbonate construction, designed for wall-mount installation
- Wall mounting
- Security lockable latches
- Available up to 48 SC
- Accepts loose tube, distribution cables
- Robust and durable construction, colour RAL7035 Grey
- Door with IP54 security mechanism
- Dimensions 450 x 180 x 150 mm.

